



PLAN VIEW - TRUCK TIRE
(N.T.S.)

1. STAFF GAUGE SHALL BE A MINIMUM 4" X 4" PRESSURE TREATED POST WITH 1/2" DIA. SCH. 40 PVC PIPE INSERTED THROUGH HOLES DRILLED THROUGH THE POST AS SHOWN ABOVE. ELEVATION MARKERS SHALL BE 1/2" DIAMETER INSTALLED AT MAX. NORMAL SURFACE LEVEL FOR WASTE STORAGE POND AND WASTE TREATMENT LAGOON AND MAX. DRAWDOWN LEVEL FOR WASTE TREATMENT LAGOON. IN ADDITION MARKERS WILL BE PLACED AT 12" INTERVALS BETWEEN THE TWO MAIN MARKERS WITH ELEVATIONS DESIGNATED IN THE TABLE TO THE RIGHT.
2. USE ONLY IN CONCRETE OR MEMBRANE LINED WASTE STORAGE POND OR LAGOON. TIRE SHALL BE PLACED IN INTIMATE CONTACT WITH THE LINER.

MARKER (FROM TOP)	ELEVATION
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	

STAFF GAUGE DETAILS	
STANDARD DWG. NO. FL-800A	
DATE 12/02	SHEET OF

REVISIONS		
DATE	APPROVED	TITLE